
APPENDIX F


STANDARD CONSTRUCTION DETAILS

Ta	h		٩f	C-	nto	nts
ıa	n	e	OΤ	l.n	nte	nts


Typical Building Sewer	S-1
Typical Grinder Pump Installation	S-2
Lateral Notes	S-3
Typical Excavation, Backfill, and Pipe Embedment Detail	S-4
New Sewer Line Parallel to Existing Water Main Detail	S-5
Concrete Encasement Detail	S-6
New Sewer Line Crossing Under Existing Water Main Detail	S-7
New Sewer Line Crossing Over Existing Water Main Detail	S-8
Concrete Anchors – Slope Breakers	S-9
Thrust Blocking	S-10
Thrust Clamping	S-11
Trench Plug Detail	S-12
Typical Manhole Detail	S-13
Cast Iron Manhole Frame and Cover	S-14
Cast Iron Watertight Manhole Frame and Cover	S-15
Manhole Frame – Anchor Bolt Detail	S-16
Manhole Base Typical Channel Configuration	S-17
Typical Outside Drop Manhole Detail	S-18
Typical Inside Drop Manhole Detail	S-19
Manhole Frame and Cover Adjustment Detail	S-20
Manhole Abandonment Detail	S-21
1,000 Gallon Grease Interceptor	S-22
Air Release-Valve Manhole	S-23
Terminal Cleanout Assembly	S-24
Intermediate Cleanout Assembly	S-25

Intermediate Cleanout Assembly	S-25
Flushing Hydrant Detail	S-26
2 Way Branch Cleanout Assembly	S-27
3 Way Branch Cleanout Assembly	S-28
Typical Tie-In to Existing Manhole Detail	S-29
Pump Station Plan View	S-30
Pump Station Section View	S-31
Pump Station Process & Instrumentation Diagram	S-32
Force Main Tracer Wire Test Station	S-33
Force Main Metering Manhole Detail	S-34





TYPICAL GRINDER PUMP LATERAL INSTALLATION - PLAN



TYPICAL GRINDER PUMP INSTALLATION - ELEVATION

SCALE: NONE

NOTES: 1. REFER TO DRAWING S-3 FOR LATERAL NOTES.

	Entech Engineering, Inc. Engineering Architecture Construction Corporate Office: 4 S. Fourth Street Reading, PA 19602 ph: 610.373.6667 fx: 610.373.7537				- WAYMART AREA AUTHORITY TYPICAL GRINDER PUMP INSTALLATION		
ENTECH	Pottsville, PA Mountaintop, PA Lititz, PA www.entecheng	ph: 570 ph: 717	0.628.5655 0.868.0275 7.626.6666 25.1372	DATE: 7/20	0/10	DRAWING NO.	
PREPARED BY MBD	CHECKED BY BAK	APPROVED BY EJP	PROJECT NO. 4152.14	SCALE: NO	NE	S-2	

LATERAL NOTES:


- ALL MATERIAL USED FOR LATERAL INSTALLATIONS SHALL BE NEW, FREE FROM DEFECTS AND CONFORM TO ALL STANDARDS SET FORTH BY WAYMART AREA AUTHORITY.
- 2. ALL LATERALS MUST BE INSPECTED BEFORE BACKFILLING. COMPLETED DRAWINGS SHOWING THE EXACT LOCATION AND DEPTH OF LINE SHALL BE SUBMITTED TO THE TOWNSHIP DURING FINAL INSPECTION OR THE LATERAL WILL NOT BE AUTHORIZED TO USE.
- ALL FEES MUST BE PAID IN PROPER AMOUNT BEFORE A CONNECTION PERMIT WILL BE ISSUED.


MATERIAL ALLOWED BY WAYMART AREA AUTHORITY FOR BUILDING GRAVITY SEWERS

- 1. PVC BELL AND SPIGOT SEWER PIPE / SDR 35.
- 2. 4" @ 1/4" / FT. MIN. GRADE 6" @ 1/8" / FT. MIN. GRADE


LOW PRESSURE:


- 1. HDPE OR PVC
- 2. MINIMUM DIAMETER: 1 1/4 INCH







TYPICAL EXCAVATION, BACKFILL & PIPE EMBEDMENT DETAIL





NEW SEWER LINE PARALLEL TO EXISTING WATER MAIN DETAIL







PIPE SIZE	"A"
4" - 16"	6"
18" - 48"	6"
54" - 84"	10"

NOTE: ALL CONCRETE SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI AT THE END OF 28 DAYS.

CONCRETE ENCASEMENT DETAIL






NOTE: ALL CONCRETE SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT THE END OF 28 DAYS.


NEW SEWER LINE CROSSING UNDER EXISTING WATER MAIN DETAIL


	Eng 4 S. Fourth	ch Engineering ineering Architecture Consi Corporate Office: a Street Reading, PA 196 373.6667 fx: 610.373.753	truction 602	WAYMART AREA AUTHORITY SEWER CROSSING UNDER EXISTING WATER MAIN DETAIL		
ENTECH	Pottsville, PA Mountaintop, PA Lititz, PA www.entecheng.	ph: 570 ph: 717	0.628.5655 0.868.0275 7.626.6666 25.1372	DATE: 7/20/10	DRAWING NO.	
PREPARED BY	CHECKED BY	APPROVED BY	PROJECT NO.	SCALE:	∃ S-7	
DYH	BAK	EJP	4152.14	NONE		



NOTE: ALL CONCRETE SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT THE END OF 28 DAYS.

NEW SEWER LINE CROSSING OVER EXISTING WATER MAIN DETAIL







CONCRETE ANCHOR NOTES:


- 1. ANCHORS ARE NOT REQUIRED ON SLOPES LESS THAN 20% UNLESS NOTED ON DRAWINGS.
- 2. PROVIDE ANCHORS ON 36' CENTERS FOR SLOPES BETWEEN 20% TO 34%.
- 3. PROVIDE ANCHORS ON 24' CENTERS FOR SLOPES BETWEEN 35% TO 50%.
- 4. PROVIDE ANCHORS ON 16' CENTERS FOR SLOPES BETWEEN 51% TO 70%.
- ALL CONCRETE SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT THE END OF 28 DAYS.

CONCRETE ANCHORS - SLOPE BREAKERS





THRUST BLOCKING FOR HORIZONTAL BENDS



ELEVATION


SECTION B-B


THRUST BLOCKING FOR VERTICAL BENDS

NOTES:


- ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT THE END OF 28 DAYS.
- 2. ALL REINFORCING STEEL SHALL BE DEFORMED BARS.
- 3. NO COUPLING OR JOINTS SHALL BE COVERED WITH CONCRETE.
- 4. INSTALL CONCRETE THRUST BLOCKS AT EACH ELBOW, TEE AND CAPPED END FITTINGS LOCATED IN THE HORIZONTAL PLANE.
- 5. HARNESS PIPE IF ORDERED BY BUILDER/DEVELOPER ENGINEER.
- 6. SIZE OF THRUST BLOCKS TO BE DETERMINED INDIVIDUALLY AT THE TIME OF CONSTRUCTION BY BUILDER/DEVELOPER ENGINEER

THRUST BLOCKING DETAILS






THRUST CLAMPING DETAIL




REQUIRED SPACING AND MATERIALS FOR TRENCH PLUGS						
TRENCH SLOPE (%) SPACING (FT) PLUG MATERIAL						
< 5	*	*				
5-15	500	** EARTH FILLED SACKS				
15-25	300	** EARTH FILLED SACKS				
25-35	200	** EARTH FILLED SACKS				
35-100	100	** EARTH FILLED SACKS				
> 100	50	CEMENT FILLED BAGS (WETTED) OR MORTARED STONE				

- * TRENCH PLUGS ARE REQUIRED AT ALL STREAM, RIVER, OR WATER-BODY CROSSINGS REGARDLESS OF TRENCH SLOPE. OTHERWISE NOT REQUIRED.
- ** TOPSOIL MAY NOT BE USED TO FILL SACKS.





D = DEPTH TO BOTTOM OF TRENCH

SECTION VIEW




TRENCH PLUG DETAIL






- ALL PIPE TO MANHOLE CONNECTIONS SHALL BE MADE WITH A CAST-IN-PLACE GASKET. (TYP) (A-LOK OR APPROVED EQUAL)
- MANHOLES EXCEEDING A DEPTH OF 16 FEET SHALL PROVIDE PRE-CAST LANDING PLATFORM.


TYPICAL MANHOLE DETAIL






NOTE: APPROXIMATE WEIGHT 500#

CAST IRON REGULAR MANHOLE FRAME & COVER






NOTES: CASTING TO BE SUPPLIED WITH BOLTED COVER AND MACHINED BEARING SURFACE.


BRIDGESTATE FOUNDARY CO, HADDONFIELD, NJ (PATTERN NO 1502 - TYPE "A" MODIFIED OR APPROVED EQUAL.

APPROXIMATE WEIGHT 500#

CAST IRON WATERTIGHT MANHOLE FRAME & COVER





2 1/2" MIN PROJECTION ABOVE FINAL COURSE OF CONCRETE OR RUBBER RISER GRADE RINGS



NOTE: FOUR (4) BOLTS REQUIRED PER MANHOLE.

MANHOLE FRAME ANCHOR BOLT DETAIL








NOTE:

1. ALL FLOW CHANNELS SHALL BE PRE-CAST BY MANUFACTURER UNLESS AUTHORIZED BY ENGINEER/AUTHORITY.


MANHOLE BASE TYPICAL CHANNEL CONFIGURATION








TYPICAL INSIDE DROP MANHOLE DETAIL





MANHOLE FRAME AND COVER ADJUSTMENT DETAIL

SCALE: NONE



DYH

Entech Engineering, Inc.

Engineering Architecture Construction

Corporate Office:
4 S. Fourth Street Reading, PA 19602
ph: 610.373.6667 fx: 610.373.7537

Pottsville, PA Mountaintop, PA

BAK

www.entecheng.com CHECKED BY APPROVED BY PROJECT NO.

EJP

ph: 570.628.5655 ph: 570.868.0275


4152.14

DATE:

MANHOLE FRAME AND COVER ADJUSTMENT DETAIL

DRAWING NO. 7/20/10 **S-20** SCALE: NONE

WAYMART AREA AUTHORITY



MANHOLE ABANDONMENT DETAIL

SCALE: NONE

Entech Engineering, Inc.

Corporate Office

4 S. Fourth Street Reading, PA 19602 ph: 610.373.6667 fx: 610.373.7537

Pottsville, PA Mountaintop, PA Lititz, PA

ph: 570.628.5655 ph: 717.626.6666 www.entech

ph: 570.868.0275

PROJECT NO.

DATE: SCALE:

7/20/10

DRAWING NO.

WAYMART AREA AUTHORITY

MANHOLE ABANDONMENT DETAIL

S-21


PREPARED BY **MBD**

CHECKED BY **BAK** APPROVED BY

EJP

4152.14


NONE




- 1. DETAIL DEPICTS A 1,000 GALLON OPERATING CAPACITY GREASE INTERCEPTOR. THE ACTUAL TYPE AND CAPACITY MUST BE DETERMINED BY OWNER AND APPROVED BY AUTHORITY.
- 2. DESIGN LOAD: H-20 TRAFFIC WITH DRY SOIL CONDITIONS (WATER LEVEL BELOW TANK) AND 1'-6' EARTH COVER.
- SUITABLE SUB-BASE BEDDED WITH GRANULAR MATERIAL SHALL BE PREPARED TO HANDLE ANTICIPATED LOADS.
- 4. FOR KITCHEN USE ONLY NOT TO BE USED WITH SEWAGE SYSTEM.
- INTERCEPTOR TO CONTAIN WATER TIGHT JOINTS.


1000 GALLON GREASE INTERCEPTOR


SCALE: NONE Entech Engineering, Inc. WAYMART AREA AUTHORITY 4 S. Fourth Street Reading, PA 19602 1000 GALLON GREASE INTERCEPTOR ph: 610.373.6667 fx: 610.373.7537 ph: 570.628.5655 Pottsville, PA DATE: DRAWING NO. Mountaintop, PA ph: 570.868.0275 ph: 717.626.6666 7/20/10 **S-22** PREPARED BY CHECKED BY APPROVED BY PROJECT NO. SCALE: NONE **MBD** EJP 4152.14 **BAK**




AIR RELEASE VALVE MANHOLE













FLUSHING HYDRANT DETAIL












NOTES:

- 1. PROPOSED SEWER PIPE INVERT ELEVATION SHALL NOT BE BELOW EXISTING SEWER INVERT ELEVATION.
- 2. PROPOSED SEWER PIPE SHALL BE LOCATED A MINIMUM OF 8" ABOVE OR BELOW EXISTING MANHOLE JOINT.
- 3. AFTER CONNECTION OF PIPE TO MANHOLE, REMOVE CONCRETE CHANNEL AS REQUIRED AND RECONSTRUCT CHANNEL.
- 4. KEEP GROUNDWATER, SURFACE WATER AND DEBRIS FROM ENTERING EXISTING FACILITIES.
- 5. MAINTAIN EXISTING FLOW DURING CONSTRUCTION.
- 6. DROPS OVER 2 FT WILL REQUIRE AN INSIDE DROP CONNECTION.


TYPICAL TIE-IN TO EXISTING MANHOLE DETAIL








FOR GENERAL ARRANGEMENT ONLY DETAIL PLANS TO BE SUBMITTED FOR REVIEW.



PUMP STATION PROCESS & INSTRUMENTATION DIAGRAM

	Ente	ch Engineerin	g, Inc.	WAYMART AREA AUTHORITY PUMP STATION PROCESS & INSTRUMENTATION DIAGRAM		
		Corporate Office: n Street Reading, PA 19 373.6667 fx: 610.373.753				
ENTECH	Pottsville, PA Mountaintop, PA Lititz, PA www.entecheng.	ph: 570 ph: 71	0.628.5655 0.868.0275 7.626.6666 25.1372	DATE: 7/20/10	DRAWING NO.	
PREPARED BY MBD	CHECKED BY BAK	APPROVED BY EJP	PROJECT NO. 4152.14	SCALE: NONE	S-32	



NOTES:

- 1. C.I. BOX SHALL BE TYLER 10" C.I. VALVE BOX TOP SECTION SLIP MODEL 10T-A WITH 5 1/4" DROP LID MODEL 14549 MARKED "SEWER"
- 2. DO NOT SPICE TRACER WIRE UNDERGROUND.
- 3. PROVIDE 3 FEET OF LOOPED WIRE WITHIN TEST STATION BOX.
- 4. SPACE TEST STATIONS 500 FEET MAX. AND AT ALL CHANGES IN FORCE MAIN DIRECTIONS
- PROVIDE METALLIC CAUTION TAPE CENTERED ON FORCE MAIN 12" BELOW FINISHED GRADE.

FORCE MAIN TRACER WIRE TEST STATION

